



RECERTIFICATION

OVERVIEW OF RECERTIFICATION REQUIREMENTS FOR HEIGHT SAFETY EQUIPMENT

AS/NZS 1891 (ALL YEARS)

Industrial fall-arrest systems and devices – Selection, use and maintenance.

6 monthly By a height safety equipment inspector.

- Harnesses, lanyards, associated personal equipment.
- Fall arrest devices (external inspection only).
- Ropes and slings.
- Horizontal or vertical lifelines – fibre rope, webbing.

12 monthly

By a height safety equipment inspector.

- Anchorages – drilled-in type or attached to timber frames.
- Anchorages other types – as recommended by the manufacturer to a maximum of 5 – yearly.
- Horizontal and vertical lifelines – steel rope or rail – as recommended by the manufacturer to a maximum of 5 – yearly.

AS/NZS 1657 (ALL YEARS)

Fixed Platforms, Walkways, Stairways and Ladders.

Testing in line with the manufacturers recommendations. RISSafety as a manufacturer recommend a 5 yearly inspection frequency on all products installed to this standard.

AS/NZS 4488.2 (ALL YEARS)

Industrial rope access systems – Selection, use and maintenance.

Permanently installed anchorages shall be inspected by a competent person at intervals not exceeding 12 months.

Additional State Requirements

WA Occupational Safety and Health Regulations 1996.

A person who, at a workplace, is an employer, the main contractor, a self-employed person or the person having control of the workplace must ensure –

- a) that an anchorage at the workplace is inspected by a competent person and –
 - i) in the case of an anchorage that is permanently fixed and in regular use, inspected at intervals not greater than 6 months; and
 - i) in the case of an anchorage that is permanently fixed but not in regular use, inspected before it is used.

NEED FURTHER GUIDANCE?

CONTACT US TODAY – 1300 663 255 or at clientservices@rissafety.com

SNAPSHOT OF CURRENT CLIENTS:

